

INTRODUCTION:

This device can monitor such parameters as:

- ECG
- RESP
- SpO2
- PR
- NIBP
- TEMP

It integrates parameter measurement module, display and recorder in one device to form compact and portable equipment. Its replaceable internal battery brings a lot of convenient for patient moving.

MAIN FEATURES:

- 12.1' TFT color LCD, multi-language interface (English, Chinese, Russian, Kazakhstan, Czech, and Slovak).
- Touch screen operation, which improves the working efficiency for medical staff.
- Fan less design, quiet, energy-saving and clean, which reduces the possibility of cross-infection.
- All-around monitor for adult, pediatric and neonate.
- With the standard interface, big character interfaces and view bed, convenient to observe.
- Waveform, parameter color, and location can be set optionally.
- Maximum 8-channel waveform synchronous display
- Display 7-lead ECG waveform on one screen.
- Adopt digital SpO2 technology, anti-motion, and anti-ambient light interference,
 and measurement can be performed under the circumstance of weak filling.
- NIBP measurement mode: Manual/AUTO/Continuous, storage for 4800-group NIBP

- Review for 71 alarm events of all parameters and 60 arrhythmia alarm events.
- Connect to Central Monitoring System by 3G, Wi-Fi or wired mode.

Drug concentration calculation and titration table functions.

- AC/DC, built-in rechargeable lithium battery achieve uninterrupted monitoring.
- Anti-high frequency surgical unit, defibrillation-proof(special leads are necessary).