Electronic pipette

dPette⁺

Multifunction Electronic Pipette

dPette

Simple Electric Pipette

Features

- High accuracy, high performance stepper motor ensures accuracy and repeatability, eliminating manual pipetting errors
- A motor driven digital control pipette with multifunction
- 2 buttons handle all operational settings
- Light weight, ergonomic design, small body dimension for easy handling that guarantees fatigue free pipetting
- Pipetting, Mixing, Stepper and Dilution(Only dPette+)
- Pipetting, Mixing(dPette)
- Adjustable speeds for aspiration and dispensing
- Li-ion battery and dual charging modes enable longer operation time
- Self calibration dPette can be connected to a PC via. USB for calibration by the user. Third party calibration is not required



Specifications

| Channels | Volume Dange | Increment | Test Volume | Error limits in accordance to ISO8655-2 | | | |
|----------|--------------|-----------|----------------|---|-------|-----------------|------|
| | Volume Range | | | accuracy error | | precision error | |
| | μL | μL | μL | μL | % | s.d.*µL | CV%* |
| 1 | 0.5-10 | 0.01 | 10 | ±0.10 | ±1.00 | 0.05 | 0.50 |
| | | | 1 | ±0.035 | ±3.50 | 0.03 | 3.00 |
| 1 | 5-50 | 0.1 | 50 | ±0.40 | ±0.80 | 0.15 | 0.30 |
| | | | 5 | ±0.15 | ±3.00 | 0.125 | 2.50 |
| 1 | 30-300 | 1 | 300 | ±1.80 | ±0.60 | 0.60 | 0.20 |
| | | | 30 | ±0.90 | ±3.00 | 0.21 | 0.70 |
| 1 | 100-1000 | 5 | 1000 | ±6.00 | ±0.60 | 2.00 | 0.20 |
| | | | 100 | ±3.00 | ±3.00 | 0.60 | 0.60 |

^{*} s.d. = Standard Deviation

^{*}CV = Coefficient of Variation

Electronic pipette



dPette is an innovative electronic pipette developed by DLAB. It combines the feature of manual pipette as ergonomic and light weight with the feature of electronic pipette as labor-saving and high performance, it offers new pipetting experience to the users.



